

PREMIUM Series

M8DBS-EX

POWER CONDITIONER

EchoStar® Approved, DishPro™ Compliant Satellite TV Protection

SPECIFICATIONS	
AC Specifications:	
Protect or Disconnect™ Circuitry	Yes
Patented Power Management Circuit*	
Overvoltage Shutoff	144V ±8\
Undervoltage Shutoff	90V ±6\
Thermal Fusing	Yes
Line Voltage	120VAC, 50/60Hz
Initial Clamping Level	200V Peak, 141V RMS
III 1449 Suppression Rating	330\
Protection Modes	L-N, L-G, N-C
Maximum Current RatingEMI/RFI Noise Filtration	15A (1800W
EMI/RFI Noise Filtration	50dB (100kHz - 1 MHz
Response Time -	< 1ns
Single Pulse Energy Dissipation	1650 Joules
Peak Impulse Current	52,000 A
Telco Protection:	
Fuseless/Auto-Resettable	Ye:
Clamping Level	260\
Canacitance	30 nf (annroy
Suppression Modes	Metallic & Longitudina
Wires Protected	2 wire, 1 pair (3,4
Connectors	RJ-11
Satellite Protection:	
Shielded	Yes
Clamping Level	27\
Frequency Range	950MHz - 2.2GHz
Insertion Loss	<1 dE
Connections	Female "F", Gold Plated
CATV Protection:	
Bi-Directional	
Shielded	Yes
Clamping Level	1.5\
Frequency Range	
Insertion Loss	<1 dE
Connections	Female "F", Gold Plated
General:	
Lightning Protection	Yes
Product Warranty	Lifetime
Connected Equipment Protection Police	yUp to \$5,000,00

Specifications subject to change without notice due to continuing product updates and improvements.

*Patent Pending



1690 Corporate Circle, Petaluma, CA 94954

800-472-5555 • 707-283-5900

www.panamax.com

Designed in U.S.A. Made in China

Model: M8DBS-EX





FEATURES & INCLUDED ACCESSORIES

Noise Filtration/Surge Protection For Home Entertainment Systems -

Including PLASMA TV, VCR, DVD, SATELLITE RECEIVER

