
## PREMIUM Series POWER CONDITIONER



## **PREMIUM** Series

## M8T-EX

## POWER CONDITIONER

Noise Filtration/Surge Protection For All Home/Office Equipment

SPECIFICAT	TONS
AC Specifications:	
Protect or Disconnect™ Circuitry	Ye:
Patented Power Management Circuit*	Ye:
Overvoltage Shutoff	144V ±8\
Undervoltage Shutoff	
Thermal Fusing	Yes
Line Voltage	120VAC, 50/60H
Initial Clamping Level	200V Peak, 141V RMS
UL 1449 Suppression Rating	330\
Protection Modes	L-N, L-G, N-G
Maximum Current Rating	15A (1800W
EMI/RFI Noise Filtration	50dB (100kHz – 1 MHz
Response Time	< 1ns
Single Pulse Energy Dissipation	1650 Joules
Peak Impulse Current	52,000 A
LAN Protection:	
Compatibility	10/100b <sup>-</sup>
Giamping Level	/\
Wires Protected	Pins 1, 2, 3, & 6
Suppression ModesD Wires Protected Connectors	RJ-45 Shared with Telco
Telco Protection:	
Fuseless/Auto-Resettable	
Clamping Level	
Capacitance	30 pf (approx.
Suppression Modes	
Wires Protected	
Connectors	_RJ-11/45 Shared with LAN
General:	
Lightning Protection	Yes
Product Warranty	Lifetime
Connected Equipment Protection Poli	cy Up to \$5,000,000

Specifications subject to change without notice due to continuing product updates and improvements.

\*Patent Pending

Designed in U.S.A. Made in China







1690 Corporate Circle, Petaluma, CA 94954 800-472-5555 • 707-283-5900

www.panamax.com

Model: M8T-EX

