

PM8C-EX

POWER CONDITIONER

Time Warner Cable® Tested & Approved Modem & TV Protection

SPECIFICATIONS AC Specifications: Protect or Disconnect™ Circuitry____ Thermal Fusing____ _____120VAC, 50/60Hz Line Voltage__ Initial Clamping Level_____200V Peak, 141V RMS UL 1449 Suppression Rating______330V Protection Modes____L-N, L-G, N-G Maximum Current Rating_____15A (1800W) EMI/RFI Noise Filtration_____45dB (100kHz - 1 MHz) Response Time____ Single Pulse Energy Dissipation_____1125 Joules ___52,000 A Peak Impulse Current____ Telco Protection: Fuseless/Auto-Resettable Yes Clamping Level_____ Capacitance ______30 pf (approx.) Suppression Modes_____Metallic & Longitudinal Wires Protected_____2 wire, 1 pair (3,4) Connectors CATV, SATELLITE & Cable Modem Protection: Bi-Directional Shielded Yes Clamping Level __ 1.5V Frequency Range_____ _____5MHz - 950MHz Insertion Loss_____ _Female "F", Gold Plated Connections General: Lightning Protection__ Product Warranty___ Lifetime* Connected Equipment Protection Policy__Up to \$100,000*

Specifications subject to change without notice due to continuing product updates and improvements.

^{*}See enclosed documentation for terms and conditions.



1690 Corporate Circle, Petaluma, CA 94954 800-472-5555 • 707-283-5900

www.panamax.com





Designed in U.S.A. Made in China

Model: PM8C-EX

