POWERMAX Series PM8DBS-EX POWER CONDITIONER

Clean & Safe Power for Audio/Video Systems DISCONNECT TECHNOLOGY EMI/RFI NOISE FILTRATION C UL US

PM8DBS-EX

POWER CONDITIONER

• EchoStar® Approved, DishPro™ Compliant Satellite TV Protection

SPECIFICATIONS AC Specifications: Protect or Disconnect™ Circuitry__ Thermal Fusing_____ Yes Line Voltage__ ____120VAC, 50/60Hz Initial Clamping Level_____200V Peak, 141V RMS UL 1449 Suppression Rating_____ 330V Protection Modes_____L-N, L-G, N-G Maximum Current Rating_____ __15A (1800W) EMI/RFI Noise Filtration_____45dB (100kHz - 1 MHz) Response Time____ Single Pulse Energy Dissipation_____ ____1125 Joules 52.000 A Peak Impulse Current____ Telco Protection: Fuseless/Auto-Resettable Clamping Level_____ 260V Capacitance _ ____30 pf (approx.) Suppression Modes_____Metallic & Longitudinal Wires Protected_____ _____2 wire, 1 pair (3,4) Connectors Satellite Protection: Shielded Clamping Level___ 27V 950MHz - 2 2GHz Frequency Range____ ___Female "F", Gold Plated Connections **CATV & Cable Modem Protection:** Bi-Directional___ Shielded Ves _1.5V Clamping Level Frequency Range_____ _____5MHz - 950MHz Insertion Loss____ <1 dB Connections__ ___Female "F", Gold Plated General: Lightning Protection__ Product Warranty__ Lifetime* Connected Equipment Protection Policy__Up to \$100,000*

Specifications subject to change without notice due to continuing product updates and improvements.

*See enclosed documentation for terms and conditions.



1690 Corporate Circle, Petaluma, CA 94954 800-472-5555 • 707-283-5900

www.panamax.com





Designed in U.S.A. Made in China

Model: PM8DBS-EX

